



राजस्थान केन्द्रीय विश्वविद्यालय  
Central University of Rajasthan  
NH-8, Bandarsindri, Kishangarh-305817, Ajmer(Raj.)

**Financial Bid**

**Name of Work: Repair & Renovation work at First Floor Administration Building, Central University of Rajasthan, Bandarsindri, Dist. Ajmer, Rajasthan.**

**NIT No. CURAJ/R/F.144/2023/4147**

**Date: 20.01.2023**

S. N	Description	Qty	Unit	Rate	Amount
1	Demolishing CLC block/Brick masonry work manually/ by mechanical means including stacking of serviceable material if any and disposal of unserviceable material within 1Kilometres lead as per direction of Engineer-in-charge.				
1.1	In cement mortar	20.70	Cum	1698.45	35150.10
2	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement, with 1:1.5:3 (1 cement: 1.5 coarse sand (zone-III)derived from natural sources: 3 graded stone aggregate 20 mm nominal size derived from natural sources).	1.29	Cum	10719.30	13868.09
3	Centering and shuttering including strutting, propping etc. and removal of form for				
3.1	Lintels, beams, plinth beams, girders, bressumers and cantilevers	14.13	Sqm	608.35	8592.94
4	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level.				
4.1	Thermo-Mechanically Treated bars of grade Fe-500D or more.	100.00	kg	89.65	8965.00
5	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :				
5.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	15.36	Cum	8288.35	127342.21
6	Providing and fixing IS : 12817 marked stainless steel butt hinges with stainless steel screws etc. complete :				
6.1	125x64x1.90 mm	12.00	Each	95.50	1146.00
7	12 mm cement plaster of mix :				
7.1	1:6 (1 cement: 6 fine sand)	46.00	Sqm	282.00	12972.00
8	15 mm cement plaster on the rough side of single or half brick wall of mix :				
8.1	1:6 (1 cement: 6 fine sand)	133.66	Sqm	324.30	43345.94
9	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	179.66	Sqm	123.85	22250.89

10	Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound ) content.				
10.1	With water thinnable cement primer on wall surface having VOC content less than 50 grams/litre	179.66	Sqm	64.45	11579.09
11	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound ) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour.				
11.1	Two coats	2112.13	Sqm	116.05	245112.45
12	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.				
12.1	Size of Tile 600x600 mm	8.00	Sqm	1416.65	11333.20
13	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
13.1	For fixed portion				
13.1.1	Powder coated aluminium (minimum thickness of powder coating 50 micron)	488.68	kg	466.3	227873.35
13.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
13.2.1	Powder coated aluminium (minimum thickness of powder coating 50 micron)	1793.92	kg	564.8	1013206.02
14	Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.				
14.1	Pre-laminated particle board with decorative lamination on both sides	100	Sqm	951.05	95105.00

15	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):				
15.1	With float glass panes of 5.00 mm thickness	150	Sqm	1325.55	198832.50
16	Filling the gap in between aluminium frame & adjacent RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.				
16.1	Upto 5mm depth and 5 mm width	150	Mtr	85.25	12787.50
17	Providing and fixing aluminium round shape handle of outer dia 100mm with SS screws etc. complete as per direction of Engineer- in-charge				
17.1	Powder coated minimum thickness 50 micron aluminium	10	Each	89.60	896.00
18	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete :				
18.1	300x16 mm	5	Each	260.30	1301.50
19	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete :				
19.1	150x10 mm	5	Each	75.55	377.75
20	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.				
20.1	Twin rubber stopper	5	Each	62.25	311.25
21	Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.	5	Each	856.30	4281.50
	Total Amount			Rs.	2096630.29
	Amount quoted in percentage, over/above/at par				

*Note: The Goods and Service Tax, Turnover Tax, Excise Duty, Work Contract Tax, Or any other Tax as applicable shall be paid by the contractor himself. The bidder shall quote his rates considering all such Taxes.*

Seal & Signature of Bidder  
Date: